

# Rugged Tablet PC EM-T86X



















#### **Functions**

- Support for Android 12 GMs system
- Support 2G/3G/4G all network communication, WiFi, Bluetooth and other communication modes
- 8500mAh battery, 9 hours of machine endurance
- IP67 high protection level, in accordance with MIL-STD-810H
- Support GPS+Glonass+Beidou, more accurate positioning
- Front 5 million, rear 13 million pixel autofocus camera for easy collection of working images and video information.
- Support 2D and other functional modules for free selection

#### **Product Six Views**



### **Specification Parameter**

Dimension	225.6 x 144.6 x 21.5 mm
Weight	Device unit 715 g
Device Color	Black
LCD	8 inch IPS 16:10, 800x1280, 700 nits
Touch Panel	10 point G+G capacitive touch screen. Gorilla glass
Camera	Front 5.0MP Rear 13.0MP, autofocus with flash
I/O	USB 2.0 x 1、Type C x 1、 SIM Card x 1, TF Card x 1 Max 512GB, 12PIN Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ3.5mm DC jack x 1
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/3A
Communicat	ion
WIFI	WiFi 802.11 a/b/g/n/ac (2.4G+5.8G)
Bluetooth	BT5.2 Transmission distance: 10m
2G/3G/4G	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B17/B28A&B LTE TDD: B38/B39/B40/B41N WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8
GNSS	Support GPS+Glonass+Beidou

Performance parameter	
CPU	ARM (OCTA Core)
os	Android 12 gMs
RAM	8GB
ROM	128GB
Battery	
Capacity	3.7V/8500mAh
Туре	Built in polymer lithium ion battery
Endurance	9hrs ( 50% volume sounds, 50% screen brightness, 1080P HD video display by default )
Data Collecti	on
NFC	Support, 13.56MHz, Support ISO/IEC 14443A protocol Card reading distance: 3–5cm
2D	Optional, Optical resolution: 5mil/ scan speed: 50 times/s
Reliability	
Operate Temperature	–20 °C ~ 60 °C
Store Temperature	–30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP67 certified, MIL-STD-810H certified
Drop Height	1.22m

### Accessories















Docking Charger TP Resist film

Back-strap Sh

Shoulder-strap Leather Cover

Car Charge

Vehicle Mount

## **Application Range**

Various modules and accessories can be selected to meet customers' application in various industries.







