

ACCENT

Rugged Tablet PC

EM-Q16



Android



IP65



GPS



NFC



1D



2D



3G/4G



WiFi



Bluetooth



Functions

- Support for Android 10 system
- Optional 3G/4G all network communication, WiFi, Bluetooth and other communication modes
- 10000mAh battery, 10 hours of machine endurance
- IP65 high protection level, in accordance with MIL-STD-810G
- Support GPS, Glonass, more accurate positioning
- Rear 13 million pixel auto focus camera, easy to collect image and video information
- Support 1D/2D, NFC and other functional modules for free selection

Product Six Views



* All technical data, specification and performance figures subject to change without notice

Specification Parameter

Basic parameters	
Dimension	280.4 x 187 x 26.6mm
Weight	Device unit 1014g
Device Color	Black
LCD	10.1 inch IPS 16:10, 1200x1920, 700nits
Touch Panel	10 point G+G capacitive touch screen Corning® Gorilla® Glass
Camera	Front 5.0MP Rear 13.0MP
I/O	HDMI 1.4a x 1, USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, TF Card x 1, 12PIN Pogo Pin x 1, DB9 RS232 x 1, RJ45 x 1, Φ3.5mm standard earphone jack x 1, Φ3.5mm DC jack x 1
Power	AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/3A

Data Collection	
NFC	Built-in, 13.56MHz, Support ISO/IEC 14443A protocol Card reading distance: 4cm
1D	Optional, Optical resolution: 5mil/ scan speed: 50 times/s
2D	Optional, Optical resolution: 5mil/ scan speed: 50 times/s
Fingerprint	Optional

Accessories



Docking Charger



Removable Battery



Back-strap



Shoulder-strap



Leather Cover



Car Charge



Quad charging



Vehicle Mount

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.



Equipment Testing



Industrial Automation



Vehicle



Medical Treatment

Performance parameter	
CPU	ARM (OCTA Core), 2.0GHz
OS	Android 10
RAM	4GB
ROM	64GB
Battery	
Capacity	3.7V/1000mAh
Type	Li_polyment, removeable battery
Endurance	10 hrs (50% volume sounds, 50% screen brightness, 1080P HD video display by default)
Communication	
WIFI	WiFi 802.11 a/b/g/n/ac (2.4G+5G)
Bluetooth	BT4.1 Transmission distance: 10m
2G/3G/4G (Optional)	CMCC 4M: LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8
GNSS	Support GPS+Glonass
Reliability	
Operate Temperature	-20 °C ~ 60 °C
Store Temperature	-30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP65 certified, MIL-STD-810G certified
Drop Height	1.22m